

NEW

FEATURES	Primo® M	Primo® XM	Primo® XXM	Primo® L	Primo® L	Primo® XL	Primo® XL	Primo® XXL
Art. no. fabric	1091029	1091021	1106232	1078703	1102536	1224093	1224096	1224105
Art. no. imitation leather	1091028	1091027	1106231	1104725				
Shock absorber								
Non-adjustable	●	●	●	●	●	●	●	●
Suspension								
Mechanical suspension	●	●	●					
Air suspension with 12 V compressor				●		●		●
Air suspension with 24 V compressor					●		●	
Low-frequency suspension						●	●	●
Suspension stroke								
110 mm						●	●	●
80 mm		●	●	●	●			
60 mm	●							
Quick weight adjustment								
Mechanical	●	●	●					
Electropneumatic				●	●	●	●	●
Setting range: 45-170 kg	●	●	●	●	●	●	●	●
Fore/aft adjustment								
210 mm	●	●	●	●	●	●	●	●
Lumbar support								
Mechanical	●	●	●	●	●	●	●	●
Adjustable backrest angle								
Setting range: -5 to +30°	●	●	●	●	●	●	●	●
Backrest extension								
Insertable	○	○		○	○	●	●	
Operator restraint system								
Static belt	○							
Duo-sensitive retractable belt	○	●	●	●	●	●	●	●
Seatbelt lock recognition					●			
Seat cushion width								
450 mm			●					●
470 mm	●	●		●	●	●	●	
OPS (Operator Presence Switch)	○	●	●	●	●	●	●	●
OPTIONS								
Document box	○	○	○	○	○	○	○	○
Armrests								
60 x 320 mm, adjustable angle	○	○	○	○	○	○	○	○
Seat heating	○	○	○	○	○	○	○	○
Strength requirement								
Complies with ISO 24135 (for forklift trucks) * ¹⁾	●	●	●	●	●	●	●	●
Complies with ISO 6683 (earth-moving machinery)		●	●	●	●	●	●	●

● Standard feature ○ Optional feature

*⁽¹⁾ Together with a restraint system